

520,993

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number  
WO 2004/004847 A1

- (51) International Patent Classification<sup>7</sup>: A63C 17/14 (81) Designated States (*national*): AT, AU, BR, CA, CH, CN, CZ, DE, DK, ES, FI, GB, HU, IL, JP, KR, MX, NO, NZ, PL, PT, RU, SE, SG, SK, US, YU, ZA.
- (21) International Application Number: PCT/CA2003/001030 (84) Designated States (*regional*): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (22) International Filing Date: 8 July 2003 (08.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/394,284 9 July 2002 (09.07.2002) US
- (71) Applicant and  
(72) Inventor: LANSEL, Toby [CA/CA]; 4152 East Pender Street, Burnaby, British Columbia V5C 2M2 (CA).
- Published:  
— with international search report  
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FOUR WHEEL MECHANICAL BRAKE SYSTEM FOR INLINE SKATES



(57) **Abstract:** A mechanical brake system for inline skates that utilizes all four wheels for braking. The brake is applied by the skater straightening the leg, or both legs if there are brakes on both skates, to a predetermined adjustable position. This causes the adjustable and spring loaded trigger rod, mounted on the pivoting ankle support behind the heel to push the brake lever that extends from behind the heel on both sides of the frame to the front where it is hingedly attached to move downwards. At the mid-point of the skate the brake rail positioned above the wheels and extending the whole length of the skate is connected to the brake lever. The downward movement of the brake lever and brake rail causes the brake rail to contact the wheels causing friction and thereby braking in direct proportion to the force by which the skater is straightening the leg(s). The brake rail is inflexible and shaped to fit the curvature of the wheels thereby facilitating even wheel wear both regarding shape and diameter. Two brackets mounted on the underside of the skate and passing through slots in the brake rail ensure centering of the brake rail. The spring loading of the trigger rod ensures smooth and controllable braking. The spring tension of the spring loaded trigger rod is adjustable so that skaters with different body weight can have optimum braking power without wheel lock-up.

BEST AVAILABLE COPY

WO 2004/004847 A1